

NEOELEC Pistol

STANLEY

DUBUIS

BPP1303 Battery operated crimping tool

NEW



HYLEC
energy solutions



SPECIFICATIONS

Crimping force	130 kN
Stroke / opening width	38 mm
Crimping range	10 – 400 mm ²
Crimping cycle (depending on cross section)	8 s up to 9 s
Number of crimps	Approx. 90
Battery voltage	18V
Battery capacity	3.0 Ah Li-Ion
Charging time	60 min.
Weight incl. battery	7 kg
Dimensions (Lxwxh)	430x310x75 mm
Ambient temperature	-10°C up to +50°C

CHARACTERISTICS

- Ergonomic design with On/ Off button
- Robust plastic housing with rubber grip handle
- Open C crimping head, 360° rotatable with interchangeable dies and wide crimping
- Maximum operating speed with high performance motor
- Balanced center of gravity for easy handling and effortless operations
- 2 stages hydraulic pump for fast feed and power stroke
- Quick motor stop function for high user safety
- 18V Li-Ion Stanley battery, high performance with short charging time
- Manual retraction when crimp is complete
- Rocking triggers system to prevent improper usage
- Simple display panel with light diode for battery charge level, crimping failure and maintenance control
- Pressure safety system to prevent over pressure failures
- Energy saving function by stopping tool after 10 min unused
- USB connection for data analysis & preventive maintenance with dedicate software
- Handling ring for safety cable or transportation

STANLEY
DUBUIS
Energy on hand

www.hylec.com.au PH +61 (0) 7 3396 2220 askhylec@hylec.com.au

REFERENCE

BPP1303A1320 Elec pistol crimping tool
10-400 mm²










ACCESSORIES

AB18LI300S	18V Li-Ion battery 3,0 Ah
AC18220S	Charger 220V 18V Li-Ion 60mn
AC18012S	Charger cigar lighter 12V-18V Li-Ion
NMKMACC002	Carrying strap
77531	Plastic case



INTERCHANGEABLES DIES SETS*

*Dies commons on tools: C130-38 Manual, XC130-38 Head

Application	Copper sleeves and lugs NFC 20.130	Copper or alu bare or insulated sleeves EDF	Copper or alu sleeves and lugs DIN48083	C-shaped connectors	Pre-rounding	Copper sleeves and lugs NFC 20.130
 Crimping Type						
Section	10 > 400 mm ²	E54 > E280	KZ6 > KZ34	C10 > C70	50 > 240 mm ²	10 > 240 mm ²

HYLEC
energy solutions

STANLEY

DUBUIS

Company of StanleyBlack&Decker Inc