

MV cables Tools

CWF3/60



Section

MV Multifunction

Application

Field
Laboratory



PRODUCT BENEFITS

Tuning of the pitch of the tool (width of the chip sheath)
Embedded wear pads to protect the tool from the contact with the outer sheath
All in one

TOOL CAPACITY

Diameter 16 - 58 mm
0,630 - 2,283 inch

Insulation thickness capacity 7 mm / 0,276 in

Remaining length of the semiconductor 30-40-45 mm /
1,181-1,575-1,772 in

TOOL DIMENSIONS

Length 305 mm

Width 115 mm

Height 165 mm

Weight without box 1,67 Kg

Packaging Box

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

Multi-function tool for outer sheath and insulation

TO DO WHAT

The CWF3/60 tools enables the user to :
Remove the outer sheath (PE-PVC-PR) with a straight and neat cut
Set the length and remove the insulation with a straight and neat cut
Other functions in option



Options

SRC-W - Scoring stylus for peelable semiconductor with chamfer on the transition

SCH-D - Cutting pencil to chamfer the end of the insulation

SFC-D07 - Scoring pencil with fixed depth 0,7mm for peelable semiconductor with chamfer

SR-W - Scoring stylus for peelable semiconductor

Spare part

KIT-MF3/40 - Protective wear pads

LCWF2 - Spare blade for outer sheath and insulation CWF3/60

BR - Thrust to set the length of insulation to be remove

VBB1 - Screw for locking the thrust

PCR - Quick set up right angled 45° handle

196855 - Straight handle M10

108098 - Clamping knob for blade

Associated tool

DSP - Peelable semiconductor lifter

C-SR - Wrench to replace the semiconductor blade

MV cables Tools
CWF3/60



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Insulation thickness capacity	Remaining length of the semiconductor	Length	Width	Height	
CWF3/60	16 - 58 mm 0,630 - 2,283 in	7 mm / 0,276 in	30-40-45 mm / 1,181-1,575-1,772 in	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	box