

**Section**

MV Outer sheath

**Application**Field  
Laboratory  
Production**PRODUCT BENEFITS**

Quick, light and easy to use

**TOOL CAPACITY**

<b>Diameter</b>	21 - 35 mm 0,827 - 1,378 inch
<b>Circular cutting thickness capacity</b>	2,8 mm / 0,110 in
<b>Longitudinal cutting thickness capacity</b>	2,8 mm / 0,110 in

**TOOL DIMENSIONS**

<b>Length</b>	240 mm
<b>Width</b>	85 mm
<b>Height</b>	80 mm
<b>Weight without box</b>	0,5 Kg
<b>Packaging</b>	Box

**ALROC SAS**

Z.I. de la Fonderie - 72160 TUFFE  
FRANCE  
Phone: +33 2 43 71 11 80  
Fax number : +33 2 43 71 16 51  
www.alroc.fr

## Pliers for MV cable outer sheath

**TO DO WHAT**

The PG2HTA/2828 enables the user to make a circular and longitudinal cut in order to remove cable's outer sheath

All cutting depth ranging from 0,5 mm / 0,019 in to 5 mm / 0,196 in are available on demand  
How to built your customized pliers : PG2HTA/yyzz  
yy = Circular cutting depth e.g : 28 = 2,8 mm / 0,110 in  
zz = Longitudinal cutting depth e.g : 28 = 2,8 mm / 0,110 in

**Options**

SGM - Large size pouch

**Spare part**

MTL1/20 - Spare blade for longitudinal cutting 2,0mm / 0,079 in  
MTC2/28 - Spare blade for circular cutting 2,8 mm / 0,110 in (x4)

**Associated tool**

MF1+/25 - Multifunction tool for bonded semiconductor  
MF2/40 - Multifonction tool for outer sheath and insulation



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Circular cutting thickness capacity	Longitudinal cutting thickness capacity	Length	Width	Height	
<b>PG2HTA/2828</b>	21 - 35 mm 0,827 - 1,378 in	2,8 mm / 0,110 in	2,8 mm / 0,110 in	240 mm 9,449 in	85 mm 3,346 in	80 mm 3,150 in	box
<b>PG3HTA/2530</b>	26 - 52 mm 1,024 - 2,047 in	2,5 mm / 0,098 in	3,0 mm / 0,118 in	265 mm 10,433 in	95 mm 3,740 in	80 mm 3,150 in	none
<b>PG3HTA/2828</b>	26 - 52 mm 1,024 - 2,047 in	2,8 mm / 0,110 in	2,8 mm / 0,110 in	240 mm 9,449 in	85 mm 3,346 in	80 mm 3,150 in	none
<b>PG3HTA/2833</b>	26 - 52 mm 1,024 - 2,047 in	2,8 mm / 0,110 in	3,3 mm / 0,130 in	265 mm 10,433 in	95 mm 3,740 in	80 mm 3,150 in	none
<b>PG4HTA/3033</b>	47 - 75 mm 1,850 - 2,953 in	3,0 mm / 0,118 in	3,3 mm / 0,130 in	300 mm 11,811 in	110 mm 4,331 in	105 mm 4,134 in	none
<b>PG4HTA/3035</b>	47 - 75 mm 1,850 - 2,953 in	3,0 mm / 0,118 in	3,5 mm / 0,138 in	300 mm 11,811 in	110 mm 4,331 in	105 mm 4,134 in	box
<b>PG5HTB/3535</b>	69 - 95 mm 2,717 - 3,740 in	3,5 mm / 0,138 in	3,5 mm / 0,138 in	360 mm 14,173 in	140 mm 5,512 in	160 mm 6,299 in	none
<b>PG6HTB/3535</b>	90 - 125 mm 3,543 - 4,921 in	3,5 mm / 0,138 in	3,5 mm / 0,138 in	515 mm 20,276 in	195 mm 7,677 in	200 mm 7,874 in	none
<b>PG6HTB/4040</b>	90 - 125 mm 3,543 - 4,921 in	4,0 mm / 0,157 in	4,0 mm / 0,157 in	515 mm 20,276 in	195 mm 7,677 in	200 mm 7,874 in	none
<b>PG7HTB/3535</b>	120 - 170 mm 4,724 - 6,693 in	3,5 mm / 0,138 in	3,5 mm / 0,138 in	515 mm 20,276 in	195 mm 7,677 in	200 mm 7,874 in	none