



PROTECT YOURSELF



LOCKOUT/TAGOUT



OPERATE

SHUNT AND REPOWERING > Clips, prick-wire, adapters



   **TW2135**

INSULATED CLIP

 Additional plug \varnothing 4 mm for potential test point.

Technical specifications : 1000 V

800A AC (2x400A)

Insulated clip 800A (2x400A) for bus bars.

For vertical bus bar (max thickness 35mm) or horizontal bus bar (max

thickness 18mm, max width 55mm).

Socket for threaded male M12 connector. Test point for 4mm safety plug.

Ref.	Electrical current
TW2135	800 A AC (2 x 400 A)



   **TW2162**

HEXAGONAL SHUNT CLIP

 Additional plug \varnothing 4 mm for potential test point.

Technical specifications : 1000 V

200A AC

Insulated shunt clip for 17 & 19mm hexagonal tightening.

Socket for threaded male M8 connector. Test point for 4mm safety plug.

Ref.	Electrical current
TW2162	200 A AC



   **TW2165**

SQUARE-END OR ROUND-END SHUNT CLIP

 Additional plug \varnothing 4 mm for potential test point.

Technical specifications : 1000 V

200A AC

Insulated shunt clip for tightening on square-end (9-10mm) or round-end (8-12mm).

Socket for threaded male M8 connector. Test point for 4mm safety plug.

Ref.	Electrical current
TW2165	200 A AC



   **TW2163**

SHUNT CLIP FOR BUS BAR

 Additional plug \varnothing 4 mm for potential test point.

Technical specifications : 1000 V

200A AC

Insulated shunt clip for tightening on posts or bus bar 20 to 30 mm.

Socket for threaded male M8 connector. Test point for 4mm safety plug.

Ref.	Electrical current
TW2163	200 A AC

PROTECT YOURSELF

LOCKOUT/TAGOUT

OPERATE

Web: www.hylec.com.au

Email: ask@hylec.com.au

Ph: +61 (0) 7 3396 2220

Fx: +61 (0) 7 3396 1217